



**HENAN SUPERIOR ABRASIVES
IMPORT & EXPORT CO., LTD.**

Tel: +86-18638638803

Web: <https://hsamaterial.com>

E-mail: sales@superior-abrasives.com

No.806,8th floor,8th building,No.68 Zhengtong road,

Erqi District Zhengzhou Henan, China



SILICA FUME TECHNICAL DATA SHEET

SILICA FUME is a very fine pozzolanic material, composed of amorphous silica produced by electric arc furnaces as a byproduct of the production of elemental silicon or ferro silicon alloys.

SILICA FUME can be used in a variety of applications such as concrete, grouts, mortars, fibre cement products, refractory oil/gas well cements, ceramics, elastomer, and polymer applications.

SILICA FUME is produced in conformance with the ASTM C1240 specifications. The quality is controlled and monitored throughout the entire production process to ensure that it meets or exceeds specification requirements.

PROPERTIES	
State	Amorphous - Sub-micron powder
Color	Gray powder
Specific Gravity	2.10 to 2.40
Solubility	Insoluble
Bulk Density - Densified	600 to 650 kg/m ³
Bulk Density - Undensified "as produced"	300 to 350 kg/m ³

SPECIFICATIONS		
Chemical Requirements	ASTM	Typical
Silicon Dioxide (SiO ₂) %	85.0% Minimum	90.42%
Moisture Content %	3.0% Maximum	0.26%
Loss on Ignition (LOI) %	6.0% Maximum	2.81%
Physical Requirements	ASTM	Typical
Oversize percent retained on 45 μm(325 sieve)	10.0% Maximum	1.43%
Accelerated Pozzolanic Strength Activity Index with Portland cement(7 day)	105.0% Minimum	118%
Surface Area	15 m ² /g Minimum	21.10 m ² /g

MECHANISM OF SILICA FUME'S POZZOLANIC REACTION IN A CEMENTITIOUS SYSTEM

SILICA FUME in contact with water goes into solution within an hour. The silica in solution forms an amorphous silica rich, Ca poor, gel on the surface of the silica fume

particles and agglomerates. After time the silica rich, Ca poor, coating dissolves and the agglomerates of silica fume reacts with free lime (CaOH_2) to form calcium silicate hydrates (CSH). This reaction is called the **pozzolanic reaction**.

SILICA FUME TECHNICAL DATA SHEET

STORAGE

SILICA FUME should be kept dry out of weather and the elements.

SAFETY AND HANDLING PRECAUTIONS

SILICA FUME is generally considered a nuisance dust. Use and handling of silica fume does not represent a health risk when normal safety rules are observed. Direct contact may cause irritation of eyes. Prolonged contact may cause skin irritation. Inhalation may cause respiratory irritation resulting in coughing and shortness of breath. This product may be harmful if swallowed. Do not get in eyes and avoid prolonged skin contact. Do not take internally. Wash thoroughly with water after handling.

Country of origin: China